


Sentry Roofing – Estimating Sheet

Sentry Shingle / Sentry Shake




Sentry Shingle / Sentry Shake panels come 15 pcs per 50 square foot box.

Round all quantities needed to the next 50 square feet.

Figure 6 screws per panel / 90 screws per box / 180 screws per Roofing SQ. Minimum of 1" long screws.

Hip & Ridge




12.75" Length, 12" Coverage

Figure 4 nailing clips and 4 screws per cap. Each cap hooks over the last.

For sealed ridge, bend and overlap panels over ridge.

For vented ridge, add 6" wide vent material.

Drip Edge




10' Length, 9' 9" Coverage

Used as a trim at the gutter end. Shake Shingles lock into the extended lip of Drip Edge.

Figure 10 screws per Drip Edge.

Gable




10' Length, 9' 9" Coverage

Used going up the Rake (sloped) end

Panels are tucked into the channel.

Figure 10 nail clips and 10 screws per Gable.

Sidewall




10' Length, 9' 9" Coverage

Used going up the side of the wall where panels run into the wall.

Tube Sealant may be needed to seal the top of Sidewall against the wall.

Figure 10 nail clips and 20 screws per Sidewall. When possible, install wall flashing behind siding.

Valley




10' Length, 9' 9" Coverage

Used on all valleys.

Figure 20 nail clips, 20 screws and 1/3 tube sealant per Valley

Shingles anchor securely into lock formed on each side of center.


Endwall / Headwall



10' Length, 9' 9" Coverage

Used where a change in roof slope occurs or where the roof terminates at a vertical wall. May have to be field adjusted to roof slope.

Anchor Strip




10' Length, 9' 9" Coverage

Mill finish. Useful in several places:

(A) Use instead of Drip Edge for areas with gutters. (B) Use above a transition to lock upper roof shingles onto. (C) Use above chimneys or skylights to hook shingles onto. (D) As a cleat for shingles above a short course roof section.


Trim Coil, 23-3/4" Wide



50' Length

Use anywhere you need to produce special flashing on the job site, including upper chimney flashing, transition flashing, and more.

Fasteners / Touch Up



Nail Clips are used for most trims, including Hip & Ridge, Gable, Sidewall, and valley.

Screws are used for panels and most trims. Some trims may require pancake head screws or flat-head nails.

Touch-Up paint is recommended for hiding any small scratches that may occur during installation.